

Printing date 30.06.2023 Version number 2 Revision: 30.06.2023

1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: G2-BOND Universal 1-PRIMER
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxiliary for dental technology
- Details of the supplier of the safety data sheet Henry Schein Dental

243-249 Bush Road, Rosedale Auckland 0632, NEW ZEALAND

Free Phone: 0800 808 855

- · Further information obtainable from: Regulatory affairs
- · Emergency telephone number: 0800 764 766 (National Poisons Centre)

2 Hazards identification

· Classification of the substance or mixture

Unst. Expl. H200 Unstable explosive.

Flam. Liq. 2 H225 Highly flammable liquid and vapour. Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms











GHS01

GHS02

2 GHS05

GHS07

307 GHS0

- · Signal word Danger
- · Hazard-determining components of labelling: 2,2'-ethylenedioxydiethyl dimethacrylate diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide
- · Hazard statements Unstable explosive.

(Contd. on page 2)

Printing date 30.06.2023 Version number 2 Revision: 30.06.2023

Trade name: G2-BOND Universal 1-PRIMER

(Contd. of page 1)

Highly flammable liquid and vapour.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

DO NOT fight fire when fire reaches explosives.

Evacuate area.

Store in accordance with local/regional/national/international regulations.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous compone	ents:	
CAS: 67-64-1	acetone	25-<50%
EINECS: 200-662-2	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 1830-78-0	2-Hydroxy-1,3 dimethacryloxypropane	≥10-<20%
EINECS: 217-388-4	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 85590-00-7	methacryloyloxydecyl dihydrogen phosphate	5-<10%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 109-16-0	2,2'-ethylenedioxydiethyl dimethacrylate	2.5-<5%
EINECS: 203-652-6	Skin Sens. 1, H317	
CAS: 75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	1-<2.5%
EINECS: 278-355-8	Repr. 2, H361	
CAS: 128-37-0	Butylated hydroxytoluene	0.5-<1%
EINECS: 204-881-4	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 72869-86-4	Urethane Dimethacrylate (UDMA)	≥0.25-<0.5%
EINECS: 276-957-5	Aquatic Chronic 2, H411; Skin Sens. 1, H317	
		(Contd. on page 3

— NZ

Printing date 30.06.2023 Version number 2 Revision: 30.06.2023

Trade name: G2-BOND Universal 1-PRIMER

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Allergic reactions
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Avoid contact with the eyes and skin.

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

(Contd. on page 4)

Printing date 30.06.2023 Version number 2 Revision: 30.06.2023

Trade name: G2-BOND_Universal_1-PRIMER

(Contd. of page 3)

· Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralising agent.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Prevent impact and friction.

Do not spray onto a naked flame or any incandescent material.

- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store in a cool place.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see section 7.

	Ingredients with limit values that require monitoring at the workplace:		
	67-64-1 acetone		
WES (New Zealand) Short-term value: 2375 mg/m³, 1000 ppm			
		Long-term value: 1185 mg/m³, 500 ppm	
		bio	
	IOELV (European Union)	Long-term value: 1210 mg/m³, 500 ppm	

· DNELs

128-37-0 Butylated hydroxytoluene

128-3/-0 Butylatea nydroxytoluene		
Dermal	DNEL dermal	0.5 mg/kg bw/day (man)
Inhalative	DNEL inhalation	3.5 mg/m3 (man)

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

(Contd. on page 5)

Printing date 30.06.2023 Version number 2 Revision: 30.06.2023

Trade name: G2-BOND Universal 1-PRIMER

(Contd. of page 4)

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- **Respiratory protection:** Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information

· Appearance:

· Form: Liquid Light yellow · Colour: · Odour: Acetone-like Not determined. · Odour threshold:

1.5-2 · pH-value at 20 °C:

· Change in condition

-95 °C · Melting point/freezing point: · Initial boiling point and boiling range: 55 °C -17 °C · Flash point:

· Flammability (solid, gas): Not applicable. · Auto-ignition temperature: Undetermined. Decomposition temperature: Not determined.

Product is not selfigniting. · Ignition temperature:

· Explosive properties: Product does not present an explosion hazard.

Risk of explosion by shock, friction, fire or other sources of ignition.

· Explosion limits:

2.6 Vol % · Lower: 13 Vol % · Upper: · Vapour pressure: Not determined. · Density at 20 °C: 0.94 g/cm^3 · Relative density Not determined. Not determined. · Vapour density Not determined. · Evaporation rate

(Contd. on page 6)

Printing date 30.06.2023 Version number 2 Revision: 30.06.2023

Trade name: G2-BOND_Universal_1-PRIMER

(Contd. of page 5)

· Solubility in / Miscibility with

water: Fully miscible.
Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.Kinematic: Not determined.

· Solvent content:

• Organic solvents: 33.0 %
 • Water: 24.0 %
 • VOC (EC) 400.6 g/l

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC30	values relevar	it for cla	ssification:
/= / / 1			

67-64-1	acetone
---------	---------

Oral LD50 5,800 mg/kg (rat (f+m))

Dermal LD50 20,000 mg/kg (rabbit)

128-37-0 Butylated hydroxytoluene

Oral |LD50| > 6,000 mg/kg (rat (f+m)) (OECD 401)

72869-86-4 Urethane Dimethacrylate (UDMA)

Oral | LD50 | >5,000 mg/kg (rat female) (OECD 401)

- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Suspected of damaging fertility or the unborn child.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Repeated dose toxicity No further relevant information available.

(Contd. on page 7)

Printing date 30.06.2023 Version number 2 Revision: 30.06.2023

Trade name: G2-BOND Universal 1-PRIMER

(Contd. of page 6)

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

128-37-0 Butylated hydroxytoluene

EC50/48h (static) 0.48 mg/l (daphnia magna) (OECD 202)

72869-86-4 Urethane Dimethacrylate (UDMA)

EC50/48h (static) >1.2 mg/l (daphnia magna) (OECD 202)

- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised.

Harmful to aquatic organisms

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

· <i>UN-</i> ∧	umber
----------------	-------

· NZS, IMDG, IATA

UN1993

· UN proper shipping name

· NZS

1993 FLAMMABLE LIQUID, N.O.S. (ACETONE), special provision 640D

(Contd. on page 8)

Printing date 30.06.2023 Version number 2 Revision: 30.06.2023

Trade name: G2-BOND_Universal_1-PRIMER

IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (ACETONE)
Transport hazard class(es)	~ / / /
NZS	
(VZ)	
	2 (E1) E1
Class Label	3 (F1) Flammable liquids. 3
IMDG, IATA	
(A)	
3	
Class	3 Flammable liquids.
Label	3
Packing group	
NZS, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33 E E C E
EMS Number: Stowage Category	F-E, <u>S-E</u> B
Transport in bulk according to Annex II of Mar	
and the IBC Code	Not applicable.
Transport/Additional information:	
NZS	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2 D/E
Tunnel restriction code	<i>D/E</i>
IMDG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
	1 71 1 0 0
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE), 3,

Printing date 30.06.2023 Version number 2 Revision: 30.06.2023

Trade name: G2-BOND Universal 1-PRIMER

(Contd. of page 8)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· New Zealan	· New Zealand Inventory of Chemicals		
67-64-1	acetone		
7732-18-5	Water		
1830-78-0	2-Hydroxy-1,3 dimethacryloxypropane		
70293-55-9	2-[(2-methyl-1-oxoallyl)oxy]ethyl 1,3-dihydro-1,3-dioxoisobenzofuran-5-carboxylate		
68611-44-9	Silane, dichlorodimethyl-, reaction products with silica		
109-16-0	2,2'-ethylenedioxydiethyl dimethacrylate		
10373-78-1	Camphorquinone		
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide		
128-37-0	Butylated hydroxytoluene		
1344-28-1	aluminium oxide		
10287-53-3	ethyl 4-dimethylaminobenzoate		
5280-78-4	CI Pigment Red 144		
72869-86-4	Urethane Dimethacrylate (UDMA)		
· HSNO Appi	HSNO Approval numbers		

67-64-1 acetone

HSR001070

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms











GHS02

GHS05 GHS07

GHS08

· Signal word Danger

· Hazard-determining components of labelling:

2,2'-ethylenedioxydiethyl dimethacrylate diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

· Hazard statements

Unstable explosive.

Highly flammable liquid and vapour.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

IF exposed or concerned: Get medical advice/attention.

(Contd. on page 10)

Printing date 30.06.2023 Version number 2 Revision: 30.06.2023

Trade name: G2-BOND Universal 1-PRIMER

(Contd. of page 9)

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

DO NOT fight fire when fire reaches explosives.

Evacuate area.

Store in accordance with local/regional/national/international regulations.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P1a EXPLOSIVES
- Qualifying quantity (tonnes) for the application of lower-tier requirements 10 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

- · Relevant phrases
- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Unst. Expl.: Explosives Unstable explosive
- Flam. Liq. 2: Flammable liquids Category 2
- Skin Corr. 1A: Skin corrosion/irritation Category 1A
- Skin Irrit. 2: Skin corrosion/irritation Category 2
- Eye Dam. 1: Serious eye damage/eye irritation Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2
- Skin Sens. 1: Skin sensitisation Category 1
- Repr. 2: Reproductive toxicity Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- Aquatic Acute 1: Hazardous to the aquatic environment acute aquatic hazard Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment long-term aquatic hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment long-term aquatic hazard Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment long-term aquatic hazard Category 3

(Contd. on page 11)

Printing date 30.06.2023 Version number 2 Revision: 30.06.2023

Trade name: G2-BOND Universal 1-PRIMER

(Contd. of page 10)

- ·Sources
- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- * * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

NZ