

Safety Data Sheet in accordance with HSNO

Date of issue: 22.07.2025

Version number 3

Revision: 22.07.2025

1 Identification of the substance or mixture and of the supplier

· **Other means of identification**

· **Trade name:** GC Fuji ORTHO LC PASTE PAK Automix Paste A

· **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Application of the substance / the mixture** Auxillary for dental technology

· **Details of the supplier of the safety data sheet**
Henry Schein Dental

243-249 Bush Road, Rosedale
Auckland 0632, NEW ZEALAND

Free Phone: 0800 808 855

· **Further information obtainable from:** Regulatory affairs

· **Emergency telephone number:** 0800 764 766 (National Poisons Centre)

2 Hazards identification

· **Classification of the substance or mixture**

Skin irritation Category 2

H315 Causes skin irritation.

Eye irritation Category 2

H319 Causes serious eye irritation.

Skin sensitisation Category 1

H317 May cause an allergic skin reaction.

Specific target organ toxicity - repeated exposure
Category 2

H373 May cause damage to the lung through
prolonged or repeated exposure. Route of
exposure: Inhalation.

Hazardous to the aquatic environment chronic Category 3H412 Harmful to aquatic life with long lasting effects.

· **Label elements**

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Exemptions**

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labelling:**

2-hydroxyethyl metacrylate

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica

Urethane Dimethacrylate (UDMA)

· **Hazard statements**

Causes skin irritation.

(Contd. on page 2)

Safety Data Sheet in accordance with HSNO

Date of issue: 22.07.2025

Version number 3

Revision: 22.07.2025

Trade name: GC_Fuji_ORTHO_LC_PASTE_PAK_Automix_Paste_A

(Contd. of page 1)

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

Do not breathe dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves / eye protection / face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/Information on ingredients

- **Chemical characterisation: Mixtures**

- **Description:**

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

- **Dangerous components:**

CAS: 868-77-9 EINECS: 212-782-2	2-hydroxyethyl metacrylate Skin irritation Category 2, H315; Eye irritation Category 2, H319; Skin sensitisation Category 1, H317	10-<25%
CAS: 68909-20-6 EINECS: 272-697-1	Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica Specific target organ toxicity - repeated exposure Category 2, H373	5-<10%
CAS: 1830-78-0 EINECS: 217-388-4	2-Hydroxy-1,3 dimethacryloxypropane Skin irritation Category 2, H315; Eye irritation Category 2, H319; Specific target organ toxicity - single exposure Category 3, H335	2.5-<5%
CAS: 72869-86-4 EINECS: 276-957-5	Urethane Dimethacrylate (UDMA) Hazardous to the aquatic environment chronic Category 2, H411; Skin sensitisation Sub-category 1B, H317	2.5-<5%
CAS: 128-37-0 EINECS: 204-881-4	Butylated hydroxytoluene Hazardous to the aquatic environment acute Category 1, H400; Hazardous to the aquatic environment chronic Category 1, H410	0.5-<1%
CAS: 7727-21-1 EINECS: 231-781-8	Potassium persulfate Oxidising solids Category 3, H272; Respiratory sensitisation Category 1, H334; Acute oral toxicity Category 4, H302; Skin irritation Category 2, H315; Eye irritation Category 2, H319; Skin sensitisation Category 1, H317; Specific target organ toxicity - single exposure Category 3, H335	0.2-<0.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- **General information:**

Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Safety Data Sheet in accordance with HSNO

Date of issue: 22.07.2025

Version number 3

Revision: 22.07.2025

Trade name: GC_Fuji_ORTHO_LC_PASTE_PAK_Automix_Paste_A

(Contd. of page 2)

If symptoms persist consult doctor.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Protect unharmed eye.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** *Allergic reactions*

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire fighting measures

· **Suitable extinguishing agents:** *CO₂, sand, extinguishing powder. Do not use water.*

· **For safety reasons unsuitable extinguishing agents:** *Water*

· **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

· **Protective equipment:** *Wear self-contained respiratory protective device.*

· **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Remove persons from danger area.

Avoid formation of dust.

Avoid contact with the eyes and skin.

Wear protective clothing.

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

· **Methods and material for containment and cleaning up:**

Pick up mechanically.

Prevent formation of dust.

Dispose of the material collected according to regulations.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety Data Sheet in accordance with HSNO

Date of issue: 22.07.2025

Version number 3

Revision: 22.07.2025

Trade name: GC_Fuji_ORTHO_LC_PASTE_PAK_Automix_Paste_A

(Contd. of page 3)

See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of dust.
Any unavoidable deposit of dust must be regularly removed.
Avoid contact with the eyes and skin.
- **Information about fire - and explosion protection:**
Protect against electrostatic charges.
Dust can combine with air to form an explosive mixture.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in unopened original receptacles.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Appropriate engineering controls** No further data; see section 7.

- **Ingredients with limit values that require monitoring at the workplace:**

128-37-0 Butylated hydroxytoluene

TWA (New Zealand)	Long-term value: 10 mg/m ³
WES (New Zealand)	Long-term value: 10 mg/m ³ dsen

- **DNELs**

128-37-0 Butylated hydroxytoluene

Dermal	DNEL dermal	0.5 mg/kg bw/day (man)
Inhalative	DNEL inhalation	3.5 mg/m ³ (man)

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Do not inhale dust / smoke / mist.
Avoid contact with the eyes and skin.
Wash hands before breaks and at the end of work.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
- **Respiratory protection:** Suitable respiratory protective device recommended.
- **Protection of hands:**



Protective gloves

(Contd. on page 5)

Safety Data Sheet in accordance with HSNO

Date of issue: 22.07.2025

Version number 3

Revision: 22.07.2025

Trade name: GC_Fuji_ORTHO_LC_PASTE_PAK_Automix_Paste_A

(Contd. of page 4)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

· **Appearance:**

· **Form:**

Pasty

· **Colour:**

Light yellow

· **Odour:**

Odourless

· **Odour threshold:**

Not determined.

· **pH-value:**

Not applicable.

· **Change in condition**

· **Melting point/freezing point:**

Undetermined.

· **Initial boiling point and boiling range:**

Undetermined.

· **Flash point:**

97 °C

· **Flammability**

Not determined.

· **Auto-ignition temperature:**

Undetermined.

· **Decomposition temperature:**

Not determined.

· **Ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product does not present an explosion hazard.

· **Explosion limits:**

· **Lower:**

Not determined.

· **Upper:**

Not determined.

· **Vapour pressure:**

Not applicable.

· **Density:**

Not determined.

· **Relative density**

Not determined.

· **Vapour density**

Not applicable.

· **Evaporation rate**

Not applicable.

· **Solubility in / Miscibility with**

· **water:**

Insoluble.

· **Partition coefficient: n-octanol/water:**

Not determined.

· **Viscosity:**

· **Dynamic:**

Not applicable.

· **Kinematic:**

Not applicable.

(Contd. on page 6)

-NZ-

Safety Data Sheet

in accordance with HSNO

Date of issue: 22.07.2025

Version number 3

Revision: 22.07.2025

Trade name: GC_Fuji_ORTHO_LC_PASTE_PAK_Automix_Paste_A

(Contd. of page 5)

· **Other information**· **Particle characteristics**SiO₂: Diameter particle structure = 2.5 - 50 nm (TEM, d50, number-based)

Diameter agglomerate = 5 - 50 nm (laser diffraction dry module, d50, volume based)

68909-20-6 Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica:

set including amorphous nanoforms; surface-treated nanoforms; Spheroidal; amorphous forms; amorphous nanoform

· **Physical state**

Solid

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Information on toxicological effects**

- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:****72869-86-4 Urethane Dimethacrylate (UDMA)**

Oral LD50 >5,000 mg/kg (rat female) (OECD 401)

128-37-0 Butylated hydroxytoluene

Oral LD50 >6,000 mg/kg (rat (f+m)) (OECD 401)

· **Primary irritant effect:**

- **Skin corrosion/irritation** Causes skin irritation.

- **Serious eye damage/irritation** Causes serious eye irritation.

- **Respiratory or skin sensitisation** May cause an allergic skin reaction.

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

- **Carcinogenicity** Based on available data, the classification criteria are not met.

- **Reproductive toxicity** Based on available data, the classification criteria are not met.

- **STOT-single exposure** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure**

May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

- **Aspiration hazard** Based on available data, the classification criteria are not met.

· **Interactive effects**

- **Repeated dose toxicity** May cause damage to organs through prolonged or repeated exposure.

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

No further relevant information available.

NZ

(Contd. on page 7)

Safety Data Sheet in accordance with HSNO

Date of issue: 22.07.2025

Version number 3

Revision: 22.07.2025

Trade name: GC_Fuji_ORTHO_LC_PASTE_PAK_Automix_Paste_A

(Contd. of page 6)

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

72869-86-4 Urethane Dimethacrylate (UDMA)
EC50/48h (static) >1.2 mg/l (daphnia magna) (OECD 202)
128-37-0 Butylated hydroxytoluene
EC50/48h (static) 0.48 mg/l (daphnia magna) (OECD 202)

- **Persistence and degradability** No further relevant information available.

- **Behaviour in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Harmful to fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

- **NZS, ADN, IMDG, IATA** not regulated

- **UN proper shipping name**

- **NZS, ADN, IMDG, IATA** not regulated

- **Transport hazard class(es)**

- **NZS, ADN, IMDG, IATA**

- **Class** not regulated

- **Packing group**

- **NZS, IMDG, IATA** not regulated

(Contd. on page 8)

Safety Data Sheet

in accordance with HSNO

Date of issue: 22.07.2025

Version number 3

Revision: 22.07.2025

Trade name: GC_Fuji_ORTHO_LC_PASTE_PAK_Automix_Paste_A

(Contd. of page 7)

- | | |
|---|-----------------|
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **New Zealand Inventory of Chemicals**

All ingredients are listed.

- **HSNO Approval numbers**

7727-21-1 Potassium persulfate

HSR001343

- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Warning

- **Hazard-determining components of labelling:**

2-hydroxyethyl metacrylate

Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica

Urethane Dimethacrylate (UDMA)

- **Hazard statements**

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

Do not breathe dust/fume/gas/mist/vapours/spray.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves / eye protection / face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

NZ

(Contd. on page 9)

Safety Data Sheet in accordance with HSNO

Date of issue: 22.07.2025

Version number 3

Revision: 22.07.2025

Trade name: GC_Fuji_ORTHO_LC_PASTE_PAK_Automix_Paste_A

(Contd. of page 8)

16 Other information

- **Relevant phrases**

H272 May intensify fire; oxidizer.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

- **Department issuing SDS:** Regulatory affairs

- **Contact:** msds@gc.dental

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Oxidising solids Category 3: Oxidizing solids – Category 3
Acute oral toxicity Category 4: Acute toxicity – Category 4
Skin irritation Category 2: Skin corrosion/irritation – Category 2
Eye irritation Category 2: Serious eye damage/eye irritation – Category 2
Respiratory sensitisation Category 1: Respiratory sensitisation – Category 1
Skin sensitisation Category 1: Skin sensitisation – Category 1
Skin sensitisation Sub-category 1B: Skin sensitisation – Category 1B
Specific target organ toxicity - single exposure Category 3: Specific target organ toxicity (single exposure) – Category 3
Specific target organ toxicity - repeated exposure Category 2: Specific target organ toxicity (repeated exposure) – Category 2
Hazardous to the aquatic environment acute Category 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Hazardous to the aquatic environment chronic Category 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Hazardous to the aquatic environment chronic Category 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Hazardous to the aquatic environment chronic Category 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- **Sources**

- ECHA (<http://echa.europa.eu/>)
- EnviChem (www.echemportal.org)

- *** Data compared to the previous version altered.**

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.