

Page 1/10

Safety Data Sheet according to WHS Regulations

Printing date 17.11.2022

Version number 2

Revision: 17.11.2022

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

· Product identifier

- Trade name: GC_RELINE_II_REMOVER_FOR_RESIN
- *Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.*
- · Application of the substance / the mixture Auxillary for dental technology
- · Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Henry Schein Halas 44 O'Dea Ave Waterloo NSW 2017 Tel: 1300 65 88 22

• Further information obtainable from: Regulatory affairs

• Emergency telephone number: 24 hours Emergency: 13 11 26.

2 Hazard(s) Identification

· Classification of the substance or mixture

Flam. Liq. 2	H225	Highly flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irritation 2A	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.

· Label elements

• *GHS label elements* The product is classified and labelled according to the Globally Harmonised System (GHS). • *Exemptions*

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5). • Hazard pictograms



· Signal word Danger

• Hazard-determining components of labelling: Methyl methacrylate

• *Hazard statements* Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation.

(Contd. on page 2)

⁻ AU

Printing date 17.11.2022

Version number 2

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 1)

May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness. • **Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. No smoking. Wear protective gloves / eye protection / face protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. • Other hazards • Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition and Information on Ingredients

· Chemical characterisation: Mixtures

• Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

• Dangerou	omponents:	
141-78-6	ethyl acetate	50-<75%
	Flam. Liq. 2, H225; Eye Irritation 2A, H319; STOT SE 3, H336	
		25-<50%
	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
• Additional information: For the wording of the listed hazard phrases refer to section 16.		

4 First Aid Measures

· Description of first aid measures

- · General information:
- Immediately remove any clothing soiled by the product. If symptoms persist consult doctor.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

- After skin contact:
- *Immediately wash with water and soap and rinse thoroughly. Seek medical treatment.*
- If skin irritation continues, consult a doctor.
- After eye contact:
- Protect unharmed eye.

Rinse opened eye for several minutes under running water. Then consult a doctor.

- After swallowing:
- Rinse out mouth and then drink plenty of water.
- If symptoms persist consult doctor.

• Information for doctor:

· Most important symptoms and effects, both acute and delayed Allergic reactions

(Contd. on page 3)

⁻ AU

Safety Data Sheet

according to WHS Regulations

Printing date 17.11.2022

Version number 2

Revision: 17.11.2022

(Contd. of page 2)

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

• *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

5 Fire Fighting Measures

· Extinguishing media

- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water
- Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire. No further relevant information available.
- Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental Release Measures

- Personal precautions, protective equipment and emergency procedures Remove persons from danger area. Keep away from ignition sources. Avoid contact with the eyes and skin. Wear protective clothing.
 Environmental precautions: Do not allow product to reach sewage system or any water course. Do not allow to penetrate the ground/soil.
 Methods and material for containment and cleaning up: Ensure adequate ventilation. Absorb liquid components with liquid-binding material. Dispose of the material collected according to regulations.
 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and Storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. Avoid contact with the eyes and skin.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Do not spray onto a naked flame or any incandescent material.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- *Requirements to be met by storerooms and receptacles: Store in a cool location.*

Printing date 17.11.2022

Version number 2

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 3)

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- *Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles.*

Protect from heat and direct sunlight.

Store in a cool place.

· Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Ingredients with limit values that require monitoring at the workplace:

141-78-6 ethyl acetate

WES Short-term value: 1440 mg/m³, 400 ppm Long-term value: 720 mg/m³, 200 ppm

80-62-6 Methyl methacrylate

WES Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sen

· DNELs

80-62-6 Methyl methacrylate

Dermal DNEL dermal 13.67 mg/kg bw/day (man) (worker, l. te., syst.)

Inhalative DNEL inhalation 208 mg/m3 (air) (worker, l. te., syst.)

• Additional information: The lists valid during the making were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.
- Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

· Respiratory protection: Suitable respiratory protective device recommended.

· Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

⁻ AU

Printing date 17.11.2022

Version number 2

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 4)

Tig

• Eye protection:

Tightly sealed goggles

Information on basic physical and chen	nical properties	
General Information		
Appearance:		
Form:	Fluid	
Colour:	Clear Emit like	
Odour: Odour threshold:	Fruit-like Not determined.	
	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/freezing point:	-83 °C (-117.4 °F)	
Initial boiling point and boiling range		
Flash point:	-1 °C (30.2 °F)	
Flammability (solid, gas):	Highly flammable.	
Ignition temperature:	Undetermined.	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	2.1 Vol %	
Upper:	12.5 Vol %	
Vapour pressure:	Not determined.	
Density:	Not determined.	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Insoluble.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	70.0 %	

AU

Safety Data Sheet

according to WHS Regulations

Printing date 17.11.2022

Version number 2

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 5)

· Other information

No further relevant information available.

10 Stability and Reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

· Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

141-78-6 ethyl acetate

Oral	LD50	4,935 mg/kg (rabbit)

Inhalative LC50/4 h 1,600 mg/l (rat (f+m))

80-62-6 Methyl methacrylate

Oral	LD50	6,000 mg/kg (rabbit)
Dermal	LD50	>5,000 mg/kg (rab)
Inhalative	LC50/4 h	>5,000 mg/kg (rab) 29.8 mg/l (rat (f+m))

· Primary irritant effect:

· Skin corrosion/irritation Irritant to skin and mucous membranes.

- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation Sensitisation possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

- *Repeated dose toxicity No further relevant information available.*
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)** No further relevant information available.

12 Ecological Information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.

(Contd. on page 7)

AU -

Printing date 17.11.2022

Version number 2

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 6)

- Additional ecological information:
- · General notes:
- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- · Results of PBT and vPvB assessment

• *PBT:* Not applicable.

· vPvB: Not applicable.

• Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

UN-Number	1111172	
ADG, IMDG, IATA	UN1173	
UN proper shipping name		
ADG IMDG, IATA	1173 ETHYL ACETATE ETHYL ACETATE	
Transport hazard class(es)		
ADG		
3		
Class	3 (F1) Flammable liquids.	
Label	3	
IMDG, IATA		
Class	3 Flammable liquids.	
Label	3	
Packing group		
ADG, IMDG, IATA	II	
Environmental hazards:		
Marine pollutant:	No	
Special precautions for user	Warning: Flammable liquids.	
Hazard identification number (Kemler code):	33	
EMS Number:	F-E,S-D	

Printing date 17.11.2022

Version number 2

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

	(Contd. of page
· Stowage Category	В
· Transport in bulk according to Annex I	I of Marpol
and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1173 ETHYL ACETATE, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Australian Inventory of Industrial Chemicals

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

80-62-6 Methyl methacrylate

· Australia: Priority Existing Chemicals

None of the ingredients is listed.

• *GHS label elements* The product is classified and labelled according to the Globally Harmonised System (GHS). • *Hazard pictograms*



· Signal word Danger

Hazard-determining components of labelling: Methyl methacrylate
Hazard statements Highly flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness.
Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. No smoking.

(Contd. on page 9)

S6, S10

AU

Printing date 17.11.2022

Version number 2

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 8)

Wear protective gloves / eye protection / face protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

· Relevant phrases

H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. · Department issuing SDS: Regulatory affairs · Contact: msds@gc.dental · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· Sources

• ECHA (http://echa.europa.eu/)

• EnviChem (www.echemportal.org)

• * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or

⁽Contd. on page 10)

⁻ AU

Printing date 17.11.2022

Version number 2

Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 9)

limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

- AU