



Printing date 08.05.2023 Version number 8 Revision: 05.05.2023

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

- · Product identifier
- · Trade name: PATTERN_RESIN_LS_Liquid
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC Australasia Dental Pty Ltd

1753 Botany Road

Banksmeadow, NSW 2019 Tel: +61 2 9301 8200

- · Further information obtainable from: Regulatory affairs
- · Emergency telephone number: 24 hours Emergency: 13 11 26.

2 Hazard(s) Identification

· Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Serious eye damage/irritation – Category 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Exemptions**

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Methyl methacrylate ethyl methacrylate 2-(2H-benzotriazol-2-yl)-p-cresol Ethyleneglycol dimethacrylate

(Contd. on page 2)

Printing date 08.05.2023 Version number 8 Revision: 05.05.2023

Trade name: PATTERN RESIN LS Liquid

(Contd. of page 1)

· Hazard statements

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition and Information on Ingredients

- · Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous	components:	
80-62-6	Methyl methacrylate	50-<75%
	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
6976-93-8	2-Methoxyethyl methacrylate	10-<25%
	Skin Irrit. 2, H315; Serious eye damage/irritation – Category 2A, H319	
97-63-2	ethyl methacrylate	5-<10%
	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Serious eye damage/irritation – Category 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	
3077-12-1	2,2'-[(4-methylphenyl)imino]bisethanol	1-<2.5%
	Acute Tox. 3, H301; Skin Irrit. 2, H315; Serious eye damage/irritation – Category 2A, H319; STOT SE 3, H335	
97-90-5	Ethyleneglycol dimethacrylate	1-<2.5%
	Skin Sens. 1, H317; STOT SE 3, H335; Flam. Liq. 4, H227	
2440-22-4	2-(2H-benzotriazol-2-yl)-p-cresol	1-<2.5%
	Acute Tox. 3, H311; Acute Tox. 3, H331; Skin Sens. 1, H317	

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

· General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

(Contd. on page 3)

Printing date 08.05.2023 Version number 8 Revision: 05.05.2023

Trade name: PATTERN RESIN LS Liquid

(Contd. of page 2)

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed Allergic reactions
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire Fighting Measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Wear protective equipment. Keep unprotected persons away.

Avoid contact with the eyes and skin.

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

Prevent seepage into sewage system, workpits and cellars.

· Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

AU

Printing date 08.05.2023 Version number 8 Revision: 05.05.2023

Trade name: PATTERN RESIN LS Liquid

(Contd. of page 3)

7 Handling and Storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

- · Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

· Additional information about design of technical facilities: No further data; see section 7.

· Ingredients with	limit values t	hat require	monitoring at	the workplace:
--------------------	----------------	-------------	---------------	----------------

80-62-6 Methyl methacrylate

WES Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sen

· DNELs

Inhalative DNEL inhalation mg/m3 (rat (f+m))

80-62-6 Methyl methacrylate

Dermal L	DNEL dermal	13.67 mg/kg bw/day (man) (worker, l. te., syst.)
Inhalative L	DNEL inhalation	208 mg/m3 (air) (worker, l. te., syst.)

- · Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Respiratory protection:

In the event that the limit exposure is exceeded, use a respiratory protective device with filter A.

Suitable respiratory protective device recommended.

(Contd. on page 5)

Printing date 08.05.2023 Version number 8 Revision: 05.05.2023

Trade name: PATTERN RESIN LS Liquid

(Contd. of page 4)

Protection of hands:



· Material of gloves

e.g. KCL Butoject 897 Butyl rubber, BR

Recommended thickness of the material: ≥ 0.29 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 16523-1:2015: Level 2).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and Chemical Properties

· General Information

· Appearance:

· Form: Liquid · Colour: Clear

Odour: Characteristic
 Odour threshold: Not determined.
 pH-value: Not determined.

· Change in condition

Melting point/freezing point:

 Initial boiling point and boiling range:
 I00 °C (212 °F)

 Flash point:

 I0 °C (50 °F)

 Flammability (solid, gas):

 Highly flammable.

 Auto-ignition temperature:

 Undetermined.

 Not determined.

• **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower: 2.1 Vol %
 Upper: 12.5 Vol %
 Vapour pressure: Not determined.

• Density at 20 °C (68 °F): 0.95 g/cm³ (7.92775 lbs/gal)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

(Contd. on page 6)

Printing date 08.05.2023 Version number 8 Revision: 05.05.2023

Trade name: PATTERN_RESIN_LS_Liquid

(Contd. of page 5)

· Solubility in / Miscibility with

• water: Fully miscible. • Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

• Dynamic: Not determined. • Kinematic: Not determined.

· Solvent content:

 \cdot VOC (EC) 0.0 g/l

• Other information No further relevant information available.

10 Stability and Reactivity

- · Reactivity No further relevant information available.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATEmix (Oral) = 5284 mg/kg

ATEmix (dermal) > 4740 mg/kg

ATEmix (inhal.) = 15 mg/l

80-62-6 M	80-62-6 Methyl methacrylate			
Oral	LD50	6,000 mg/kg (rabbit)		
Dermal	LD50	>5,000 mg/kg (rab)		
Inhalative	LC50/4 h	29.8 mg/l (rat (f+m))		
97-63-2 eti	97-63-2 ethyl methacrylate			
Oral	LD50	13,424 mg/kg (rat (f+m))		
Inhalative	LC50/4 h	55 mg/l (rat (f+m))		
97-90-5 Et	97-90-5 Ethyleneglycol dimethacrylate			
Oral	LD50	8,700 mg/kg (rat (f+m))		
Dermal	LD50	>2,000 mg/kg (rat (f+m))		
2440-22-4	2440-22-4 2-(2H-benzotriazol-2-yl)-p-cresol			
Oral	LD50	10,000 mg/kg (rat (f+m))		
Inhalative	LC50/4 h	0.59 mg/l (rat (f+m))		

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 08.05.2023 Version number 8 Revision: 05.05.2023

Trade name: PATTERN_RESIN_LS_Liquid

(Contd. of page 6)

- · STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

12 Ecological Information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

4 Transport information	
· UN-Number · ADG, IMDG, IATA	UN1247
· UN proper shipping name	
ADG	1247 METHYL METHACRYLATE MONOMER STABILIZED
· IMDG, IATA	METHYL METHACRYLATE MONOMER, STABILIZED

F--8- -

Printing date 08.05.2023 Version number 8 Revision: 05.05.2023

Trade name: PATTERN_RESIN_LS_Liquid

	(Contd. of page
Transport hazard class(es)	
ADG	
Class Label	3 (F1) Flammable liquids.
IMDG, IATA	
Class Label	3 Flammable liquids. 3
Packing group ADG, IMDG, IATA	II
Environmental hazards: Marine pollutant:	No
Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Stowage Code	Warning: Flammable liquids. 33 F-E,S-D C SWI Protected from sources of heat. SW2 Clear of living quarters.
Transport in bulk according to Annex II of Manand the IBC Code	
Transport/Additional information:	
ADG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category Tunnel restriction code	D/E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOME. STABILIZED, 3, II

Printing date 08.05.2023 Version number 8 Revision: 05.05.2023

Trade name: PATTERN_RESIN_LS_Liquid

(Contd. of page 8)

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sajety, nea	uth and environmental regulations/legistation specific for the substance or mix	ture	
· Australian	Inventory of Industrial Chemicals		
80-62-6	Methyl methacrylate		
6976-93-8	2-Methoxyethyl methacrylate		
97-63-2	ethyl methacrylate		
3077-12-1	2,2'-[(4-methylphenyl)imino]bisethanol		
97-90-5	Ethyleneglycol dimethacrylate		
2440-22-4	2-(2H-benzotriazol-2-yl)-p-cresol		
128-37-0	Butylated hydroxytoluene		
· Standard f	or the Uniform Scheduling of Medicines and Poisons		
80-62-6 M	lethyl methacrylate	S6, S10	
97-63-2 et	hyl methacrylate	<i>S5</i>	
· Australia:	Priority Existing Chemicals		
None of the	None of the ingredients is listed		

None of the ingredients is listed.

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Methyl methacrylate

ethyl methacrylate

2-(2H-benzotriazol-2-yl)-p-cresol

Ethyleneglycol dimethacrylate

· Hazard statements

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 10)

Printing date 08.05.2023 Version number 8 Revision: 05.05.2023

Trade name: PATTERN RESIN LS Liquid

(Contd. of page 9)

- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

H227 Combustible liquid.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

· Department issuing SDS: Regulatory affairs

· Contact: msds@gc.dental

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 4: Flammable liquids - Category 4

Acute Tox. 3: Acute toxicity - Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Serious eye damage/irritation - Category 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

·Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)

* Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.