

Printing date 03.08.2018 Version number 3 Revision: 20.01.2016

SECTION 1: Identification

- · 1.1 Product identifier
- · Trade name: GC CERAMIC PRIMER B
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxiliary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V.

Interleuvenlaan 33

B-3001 Leuven

Tel. +32/(0)16/74.10.00

Fax + 32/(0)16/40.26.84

msds@gc.dental

- · Information department: Regulatory affairs
- · 1.4 Emergency telephone number: International: +01-813-248-0585 (ChemTel Inc.)

SECTION 2: Hazard(s) identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labeled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

Methyl methacrylate

2-hydroxyethyl metacrylate

Urethane Dimethacrylate (UDMA)

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 03.08.2018 Version number 3 Revision: 20.01.2016

Trade name: GC CERAMIC PRIMER B

(Contd. of page 1)

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

2 % of the mixture consists of component(s) of unknown toxicity.

Contains 2 % of components with unknown hazards to the aquatic environment.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

| · Dangerous o | components: | |
|---------------|--|---------|
| 80-62-6 | Methyl methacrylate | 25-<50% |
| | Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 | |
| 64-17-5 | ethyl alcohol | 25-<50% |
| | Flam. Liq. 2, H225 | |
| 868-77-9 | 2-hydroxyethyl metacrylate | 10% |
| | Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 | |
| 72869-86-4 | Urethane Dimethacrylate (UDMA) | 5-<10% |
| | Skin Sens. 1, H317 | |

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First-aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

(Contd. on page 3)

Printing date 03.08.2018 Version number 3 Revision: 20.01.2016

Trade name: GC CERAMIC PRIMER B

(Contd. of page 2)

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Fire-fighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources

Avoid contact with the eyes and skin.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the collected material according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

(Contd. on page 4)

Printing date 03.08.2018 Version number 3 Revision: 20.01.2016

Trade name: GC CERAMIC PRIMER B

(Contd. of page 3)

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray on a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · 8.1 Control parameters

| | | 1 | .1 | • •, • | , ,1 1 1 |
|-----------|--------------|-------------|---------------|----------------|---------------------|
| · Lamnana | onte with | limit value | c that roan | iro manitarino | g at the workplace: |
| Compone | TILLS TYLLIL | unu rauc | s iiiui i cyu | | , at the workplace. |

80-62-6 Methyl methacrylate

IOELV Short-term value: 100 ppm Long-term value: 50 ppm

· DNELs

80-62-6 Methyl methacrylate

| Dermal | DNEL dermal | 13.67 mg/kg bw/day (man) (worker, l. te., syst.) |
|------------|-----------------|--|
| Inhalative | DNEL inhalation | 208 mg/m3 (air) (worker, l. te., syst.) |

- · Additional information: The lists that were valid during the creation were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

- · Breathing equipment: Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 03.08.2018 Version number 3 Revision: 20.01.2016


Trade name: GC CERAMIC PRIMER B

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



| 0.1 Information on basis abusis at | and chamical properties |
|--|---|
| 9.1 Information on basic physical a General Information | ina cnemicai properties |
| Appearance: | |
| Form: | Liquid |
| Color: | Light yellow |
| Odor: | Ester-like |
| Odor threshold: | Not determined. |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | 78 °C |
| Flash point: | 13 °C |
| Flammability (solid, gaseous): | Not applicable. |
| Ignition temperature: | Undetermined. |
| Decomposition temperature: | Not determined. |
| Auto igniting: | Product is not selfigniting. |
| Danger of explosion: | Product does not present an explosion hazard. |
| Explosion limits: | |
| Lower: | Not determined. |
| Upper: | Not determined. |
| Vapor pressure: | Not determined. |
| Density at 20 °C: | 0.94 g/cm³ |
| Relative density | Not determined. |
| Vapor density | Not determined. |
| Evaporation rate | Not determined. |
| Solubility in / Miscibility with | |
| Water: | Fully miscible. |
| Partition coefficient (n-octanol/wat | t er): Not determined. |
| Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |

Printing date 03.08.2018 Version number 3 Revision: 20.01.2016

Trade name: GC CERAMIC PRIMER B

(Contd. of page 5)

· Solvent content:

VOC (EC) 310.2 g/l

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· LD/LC50 values that are relevant for classification:

- · 11.1 Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.

| - | 112/1200 futures that are recertainty of classification. | | | |
|---|--|----------|------------------------|--|
| ć | 80-62-6 Methyl methacrylate | | | |
| (| Oral | LD50 | 6000 mg/kg (rabbit) | |
| i | Dermal | LD50 | >5000 mg/kg (rab) | |
| i | Inhalative | LC50/4 h | 29.8 mg/l (rat (f+m)) | |
| (| 64-17-5 ethyl alcohol | | | |
| (| Oral | LD50 | 7060 mg/kg (rat (f+m)) | |
| i | Inhalative | LC50/4 h | 20000 mg/l (rat (f+m)) | |

72869-86-4 Urethane Dimethacrylate (UDMA)

Oral LD50 > 5000 mg/kg (rat female) (OECD 401)

- · Primary irritant effect:
- · on the skin:

Causes skin irritation.

· on the eye:

Causes serious eye irritation.

- · Sensitization:
- May cause an allergic skin reaction.
- · Additional toxicological information:
- · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

(Contd. on page 7)

Printing date 03.08.2018 Version number 3 Revision: 20.01.2016

Trade name: GC CERAMIC PRIMER B

(Contd. of page 6)

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

72869-86-4 Urethane Dimethacrylate (UDMA)

EC50/48h (static) > 1.2 mg/l (daphnia magna) (OECD 202)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

| · European | · European waste catalogue | | | |
|------------|---|--|--|--|
| | WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except | | | |
| | kitchen and restaurant wastes not arising from immediate health care) | | | |
| 18 01 00 | wastes from natal care, diagnosis, treatment or prevention of disease in humans | | | |
| 18 01 06* | chemicals consisting of or containing hazardous substances | | | |

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

| SECTION 14: Transport information | | |
|---|--|--|
| · 14.1 UN-Number · ADR, IMDG, IATA | UN1993 | |
| · 14.2 UN proper shipping name · DOT | Flammable liquids, n.o.s. (Methyl methacrylate monomer, stabilized, Ethanol) | |

(Contd. on page 8)

Printing date 03.08.2018 Version number 3 Revision: 20.01.2016

Trade name: GC CERAMIC PRIMER B

| | (Contd. of page 7 |
|---|--|
| · ADR · IMDG, IATA | 1993 FLAMMABLE LIQUID, N.O.S. (METHYI METHACRYLATE MONOMER, STABILIZED, ETHANOI SOLUTION), special provision 640D FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED, ETHANOL SOLUTION) |
| · 14.3 Transport hazard class(es) | |
| $\cdot ADR$ | |
| | |
| · Class · Label | 3 (F1) Flammable liquids 3 |
| · IMDG, IATA | |
| | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · 14.4 Packing group · ADR, IMDG, IATA | II |
| · 14.5 Environmental hazards: · Marine pollutant: | No |
| · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: | Warning: Flammable liquids 33 F-E,S-E |
| · 14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code | ex II of Not applicable. |
| · Transport/Additional information: | ** |
| · ADR · Limited quantities (LQ) · Excepted quantities (EQ) | 1L Code: E2 Maximum net quantity per inner packaging: 30 ml |
| · Transport category · Tunnel restriction code | Maximum net quantity per outer packaging: 500 ml 2 D/E |
| · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |

Printing date 03.08.2018 Version number 3 Revision: 20.01.2016

Trade name: GC CERAMIC PRIMER B

(Contd. of page 8)

· UN "Model Regulation":

UN 1993 FLAMMABLE LIQUID, N.O.S., SPECIAL PROVISION 640D (METHYL METHACRYLATE MONOMER, STABILIZED, ETHANOL SOLUTION), 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 Methyl methacrylate

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

64-17-5 ethyl alcohol

· Carcinogenic categories

| · EPA (Environmental Protection Agency) | |
|--|-------|
| 80-62-6 Methyl methacrylate | E, NL |
| · TLV (Threshold Limit Value established by ACGIH) | |
| 80-62-6 Methyl methacrylate | A4 |

- 80-62-6
 Methyl methacrylate
 A4

 64-17-5
 ethyl alcohol
 A3

 128-37-0
 Butylated hydroxytoluene
 A4
- · MAK (German Maximum Workplace Concentration)

| 64-17-5 | ethyl alcohol | 5 |
|----------|--------------------------|---|
| 128-37-0 | Butylated hydroxytoluene | 4 |

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 03.08.2018 Version number 3 Revision: 20.01.2016

Trade name: GC CERAMIC PRIMER B

(Contd. of page 9)

SECTION 16: Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

Flam. Liq. 2: Flammable liquids - Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)

* Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.