

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.04.2024

Version number 4 (replaces version 3)

Revision: 10.04.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier • Trade name: EQUIA Forte Coat · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Auxillary for dental technology • 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: GC EUROPE N.V. Interleuvenlaan 33 B-3001 Leuven Tel. +32/(0)16/74.10.00 Fax + 32/(0)16/40.26.84msds@gc.dental · Further information obtainable from: Regulatory affairs · 1.4 Emergency telephone number: National poison center for United Kingdom of Great Britain and Northern Ireland: Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383 Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180 Penarth: +44 292 071 55 54 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 Flam. Liq. 2 H225 Highly flammable liquid and vapour. Skin Irrit. 2 H315 Causes skin irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. Repr. 2 H361f Suspected of damaging fertility. STOT SE 3 H335 May cause respiratory irritation. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5). • Hazard pictograms



⁻ GB

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.04.2024

Version number 4 (replaces version 3)

Revision: 10.04.2024

Trade name: EQUIA_Forte_Coat

Signal word Da	(Contd. of page 1)
0	ining components of labelling:
Methyl methacr	
	rimethylbenzoyl)phosphine oxide
Hazard stateme	
	ammable liquid and vapour.
H315 Causes s	
	se an allergic skin reaction.
•	d of damaging fertility.
<i>v</i> 1	se respiratory irritation.
	to aquatic life with long lasting effects.
Precautionary s	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P.	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water
	[or shower].
P308+P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see on this label).
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
2.3 Other hazar	<i>ids</i>
Descelles of DDT	and a Dr. D. and a second and

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

*

· Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

Methyl methacrylate Flam. Lig. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE	25-<50%
substance with a Community workplace exposure limit	
silicon dioxide Nanoform: set including amorphous nanoforms non-surface-treated nanoforms Shape: Spheroidal Structure: amorphous forms Crystallinity: amorphous nanoform	10-<25%
diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide Repr. 2, H361f	≥3-<5%
Butylated hydroxytoluene Aquatic Acute I, H400; Aquatic Chronic I, H410 Substance identified as having endocrine disrupting properties (II)	0.5-<1%
si Na di Re Bi	licon dioxide anoform: set including amorphous nanoforms non-surface-treated nanoforms Shape: Spheroidal Structure: amorphous forms Crystallinity: amorphous nanoform phenyl(2,4,6-trimethylbenzoyl)phosphine oxide epr. 2, H361f utylated hydroxytoluene quatic Acute 1, H400; Aquatic Chronic 1, H410

Printing date 10.04.2024

Version number 4 (replaces version 3)

Revision: 10.04.2024

Trade name: EQUIA_Forte_Coat

• Additional information: For the wording of the listed hazard phrases refer to section 16.

 $(Contd. \ of page \ 2)$

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · General information:
- Immediately remove any clothing soiled by the product.
- If symptoms persist consult doctor.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

• After eye contact:

Rinse opened eye for several minutes under running water.

- If symptoms persist consult doctor.
- After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions

- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire. No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Remove persons from danger area. Keep away from ignition sources. Avoid contact with the eyes and skin. Wear protective clothing.
6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to penetrate the ground/soil. In case of seepage into the ground inform responsible authorities.

(Contd. on page 4)

Printing date 10.04.2024

Version number 4 (replaces version 3)

Revision: 10.04.2024

(Contd. of page 3)

Trade name: EQUIA_Forte_Coat

• 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

• **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. Avoid contact with the eyes and skin.

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Do not spray onto a naked flame or any incandescent material.

 \cdot 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- *Requirements to be met by storerooms and receptacles:* Store in a cool location. Store only in unopened original receptacles.
- · Information about storage in one common storage facility: Store away from foodstuffs.

• Further information about storage conditions:

Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. Store in a cool place.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

80-62-6 Methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm

· DNELs

80-62-6 Methyl methacrylate

Dermal DNEL dermal 13.67 mg/kg bw/day (man) (worker, l. te., syst.)

Inhalative DNEL inhalation 208 mg/m3 (air) (worker, l. te., syst.)

128-37-0 Butylated hydroxytoluene

Dermal DNEL dermal 0.5 mg/kg bw/day (man)

Inhalative DNEL inhalation 3.5 mg/m3 (man)

• Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)

GB

Printing date 10.04.2024

*

Version number 4 (replaces version 3)

Revision: 10.04.2024

Trade name: EQUIA_Forte_Coat

• Decomposition temperature:

· pH

· Viscosity:

· Dynamic:

· Kinematic viscosity

	(Contd. of page 4)
- 8.2 Exposure controls	
• Appropriate engineering controls No further data; see s	
Individual protection measures, such as personal prote	ctive equipment
General protective and hygienic measures:	
The usual precautionary measures are to be adhered to	when handling chemicals.
Avoid contact with the eyes and skin.	
Wash hands before breaks and at the end of work.	
Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothin	a
• Respiratory protection: Suitable respiratory protective d	
· Hand protection	evice recommended.
Protective gloves	
· Material of gloves	
	d on the material, but also on further marks of quality and
	ict is a preparation of several substances, the resistance of
the glove material can not be calculated in advance and	
· Penetration time of glove material	has merejore to be encerca prior to the application.
	the manufacturer of the protective gloves and has to be
observed.	
· Eye/face protection	
Tightly sealed goggles	
SECTION 9: Physical and chemical properties	
9.1 Information on basic physical and chemical proper General Information	ues
	Fluid
· Colour:	Clear
· Odour:	Pungent
• Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Undetermined.
· Flammability	
	Highly flammable.
· Lower and upper explosion limit	Highly flammable.
• Lower and upper explosion limit • Lower:	Highly flammable. 2.1 Vol %
	2.1 Vol % 12.5 Vol %
· Lower:	2.1 Vol % 12.5 Vol % 10 °C
· Lower: · Upper:	2.1 Vol % 12.5 Vol %

Not determined.

Not determined.

Not determined.

Not determined.

(Contd. on page 6) GB

Printing date 10.04.2024

Version number 4 (replaces version 3)

Revision: 10.04.2024

Trade name: EQUIA_Forte_Coat

	(Contd. of page
Solubility	
water:	Insoluble.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	$1.06 \ g/cm^3$
Relative density	Not determined.
Vapour density	Not determined.
Particle characteristics	SiO2: Diameter particle structure = $2.5 - 50$ nm (TEN)
	d50, number-based)
	Diameter agglomerate = $5 - 50$ mm (laser diffraction d
	module, d50, volume based)
	7631-86-9 silicon dioxide:
	set including amorphous nanoforms
	non-surface-treated nanoforms
	Shape: Spheroidal
	Structure: amorphous forms
	Crystallinity: amorphous nanoform
9.2 Other information	
Appearance:	
Form:	Liquid
Important information on protection of health of	
environment, and on safety.	<i>th</i> u
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not seting ming. Product does not present an explosion hazard.
Solvent content:	Troduci does not present un explosion nazura.
VOC (EC)	$0.0 \ g/l$
Change in condition	0.0 g/l
Evaporation rate	Not determined.
•	Not determined.
Information with regard to physical hazard classes	17 . 1
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable ga	
in contact with water	Void
	Void
Oxidising liquids	
Oxidising liquids Oxidising solids	Void
Oxidising liquids Oxidising solids Organic peroxides	
Oxidising liquids Oxidising solids	Void

(Contd. on page 7)

Printing date 10.04.2024

Version number 4 (replaces version 3)

Revision: 10.04.2024

Trade name: EQUIA_Forte_Coat

(Contd. of page 6)

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

80-62-6 Methyl methacrylate

Oral LD50 6,000 mg/kg (rabbit)

Dermal LD50 > 5,000 mg/kg (rab)

Inhalative LC50/4 h 29.8 mg/l (rat (f+m))

7631-86-9 silicon dioxide

Oral LD50 10,000 mg/kg (rat (f+m))

128-37-0 Butylated hydroxytoluene

Oral LD50 >6,000 mg/kg (rat (f+m)) (OECD 401)

· Skin corrosion/irritation Causes skin irritation.

· Respiratory or skin sensitisation May cause an allergic skin reaction.

· Reproductive toxicity Suspected of damaging fertility.

· STOT-single exposure May cause respiratory irritation.

• Additional toxicological information:

• *Repeated dose toxicity No further relevant information available.*

• CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) No further relevant information available.

• 11.2 Information on other hazards

• Endocrine disrupting properties

128-37-0 Butylated hydroxytoluene

List II

SECTION 12: Ecological information

•	12.1	Toxicity
---	------	----------

· Aquatic toxicity:

128-37-0 Butylated hydroxytoluene

EC50/48h (static) 0.48 mg/l (daphnia magna) (OECD 202)

· 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

· 12.5 Results of PBT and vPvB assessment

• *PBT:* Not applicable.

(Contd. on page 8)

GB -

Printing date 10.04.2024

Version number 4 (replaces version 3)

Revision: 10.04.2024

Trade name: EQUIA_Forte_Coat

(Contd. of page 7)

- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- Remark: Harmful to fish
- Additional ecological information:
- General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1247
14.2 UN proper shipping name ADR	1247 METHYL METHACRYLATE MONOMER
	STABILIZED
IMDG, IATA	METHYL METHACRYLATE MONOMER, STABILIZED
14.3 Transport hazard class(es)	
ADR	
Class Label	3 (F1) Flammable liquids. 3
IMDG, LATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	II

Printing date 10.04.2024

Version number 4 (replaces version 3)

Revision: 10.04.2024

Trade name: EQUIA_Forte_Coat

	(Contd. of page a
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Stowage Code	Warning: Flammable liquids. 33 F-E,S-D C SW1 Protected from sources of heat. SW2 Clear of living quarters.
14.7 Maritime transport in bulk according to IM instruments	<i>10</i> Not applicable.
Transport/Additional information:	Temperature control is not required, in regards to Specia Provision 386. Product uses chemical stabilization.
ADR Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category Tunnel restriction code	2 D/E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER STABILIZED, 3, II

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture • Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

(Contd. on page 10)

GB

Printing date 10.04.2024

Version number 4 (replaces version 3)

Revision: 10.04.2024

Trade name: EQUIA_Forte_Coat

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 9)

SECTION 16: Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

- *H410 Very toxic to aquatic life with long lasting effects.*
- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

- IMDG. International Maritime Code for Dangerous Go
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (UK REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids Category 2
- Skin Irrit. 2: Skin corrosion/irritation Category 2
- Skin Sens. 1: Skin sensitisation Category 1
- Repr. 2: Reproductive toxicity Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- Aquatic Acute 1: Hazardous to the aquatic environment acute aquatic hazard Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment long-term aquatic hazard Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment long-term aquatic hazard Category 3
- Sources
- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- * * Data compared to the previous version altered.
- This version replaces all previous versions.
- Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.