

Revision: 22.06.2017 Printing date 02.08.2018 Version number 3

SECTION 1: Identification

- · 1.1 Product identifier
- · Trade name: GC Tray Adhesive
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxiliary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V. Interleuvenlaan 33 B-3001 Leuven

Tel. +32/(0)16/74.10.00 Fax + 32/(0)16/40.26.84

msds@gc.dental

- · Information department: Regulatory affairs
- · 1.4 Emergency telephone number: International: +01-813-248-0585 (ChemTel Inc.)

SECTION 2: Hazard(s) identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Exempt from requirements - product regulated as a medical device or an in vitro diagnostic medical device.

H225 Highly flammable liquid and vapour. Flam. Liq. 2

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to the central nervous system and the peripheral nervous system

through prolonged or repeated exposure. Route of exposure: Inhalation.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

Exempt from requirements - product regulated as a medical device or an in vitro diagnostic medical device. The product is classified and labeled according to the CLP regulation.

· Hazard pictograms









GHS02

GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling: toluene

(Contd. on page 2)

Printing date 02.08.2018 Version number 3 Revision: 22.06.2017

Trade name: GC Tray Adhesive

(Contd. of page 1)

Salicylic acid

acetone

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the central nervous system and the peripheral nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves / eye protection / face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterization: Mixtures

· Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:	
67-64-1 acetone	25-<50%
Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
108-88-3 toluene	10-<25%
Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	

(Contd. on page 3)

Printing date 02.08.2018 Version number 3 Revision: 22.06.2017

Trade name: GC Tray Adhesive

		(Contd. of page 2)
78-93-3	butanone	10-<25%
	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
69-72-7	Salicylic acid	≥3-<5%
	Eye Dam. 1, H318; Acute Tox. 4, H302	
1314-13-2	zinc oxide	1-<2.5%
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
· Additiona	l information: For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First-aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water.

If symptoms persist consult doctor.

Call a doctor immediately.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Fire-fighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Remove persons from danger area.

(Contd. on page 4)

Printing date 02.08.2018 Version number 3 Revision: 22.06.2017

Trade name: GC Tray Adhesive

(Contd. of page 3)

Keep away from ignition sources

Avoid contact with the eyes and skin.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the collected material according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Do not inhale dust / smoke / mist.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray on a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · 8.1 Control parameters
- · Components with limit values that require monitoring at the workplace:

67-64-1 acetone

IOELV Long-term value: 1210 mg/m³, 500 ppm

(Contd. on page 5)

Printing date 02.08.2018 Version number 3 Revision: 22.06.2017

Trade name: GC Tray Adhesive

| 108-88-3 toluene | 10ELV | Short-term value: 384 mg/m³, 100 ppm | Long-term value: 192 mg/m³, 50 ppm | Skin |

78-93-3 butanone

IOELV Short-term value: 900 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work. Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

- · Breathing equipment: Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid Color: Blue

Odor: CharacteristicOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

(Contd. on page 6)

Printing date 02.08.2018 Version number 3 Revision: 22.06.2017

Trade name: GC Tray Adhesive

		(Contd. of page
Boiling point/Boiling range:	55 °C	
· Flash point:	-17 °C	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	Undetermined.	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	1.8 Vol %	
Upper:	13 Vol %	
· Vapor pressure:	Not determined.	
· Density at 20 °C:	0.7615 g/cm³	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Insoluble.	
· Partition coefficient (n-octanol/wa	ter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	52.5 %	
VOC (EC)	399.9 g/l	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 02.08.2018 Version number 3 Revision: 22.06.2017

Trade name: GC Tray Adhesive

(Contd. of page 6)

		(Conta. of page o)
· LD/LC50 values that are relevant for classification:		
67-64-1 acetone		
Oral	LD50	5,800 mg/kg (rat (f+m))
Dermal	LD50	20,000 mg/kg (rabbit)
78-93-3	butano	one
Oral	LD50	3,300 mg/kg (rat (f+m))
Dermal	LD50	5,000 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin:

Causes skin irritation.

on the eye:

Causes serious eye damage.

- · Sensitization: Based on available data, the classification criteria are not met.
- · Additional toxicological information:

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- · Repeated dose toxicity May cause damage to organs through prolonged or repeated exposure.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure

May cause damage to the central nervous system and the peripheral nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

· Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)

Version number 3 *Printing date 02.08.2018* Revision: 22.06.2017

Trade name: GC Tray Adhesive

(Contd. of page 7)

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
	WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care)	
18 01 00	wastes from natal care, diagnosis, treatment or prevention of disease in humans	
18 01 06*	chemicals consisting of or containing hazardous substances	

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name DOT ADR IMDG, IATA	Flammable liquids, n.o.s. (Acetone, Ethyl methyl ketone) 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, ETHY METHYL KETONE (METHYL ETHYL KETONE)), speci provision 640D FLAMMABLE LIQUID, N.O.S. (ACETONE, ETHYL METHY
14.3 Transport hazard class(es)	KETONE (METHYL ETHYL KETONE))
ADR	
Class	3 (F1) Flammable liquids
IMDG, IATA	3
Class	3 Flammable liquids
Ciuss	

Printing date 02.08.2018 Version number 3 Revision: 22.06.2017

Trade name: GC Tray Adhesive

	(Contd. of page
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	B
· 14.7 Transport in bulk according to Anne	ex II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· <i>ADR</i>	
· Limited quantities (LQ)	IL
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUID, N.O.S., SPECIA
<u> </u>	PROVISION 640D (ACETONE, ETHYL METHYL KETON
	(METHYL ETHYL KETONE)), 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

108-88-3 toluene 78-93-3 butanone 1314-13-2 zinc oxide

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 10)

Printing date 02.08.2018 Version number 3 Revision: 22.06.2017

Trade name: GC Tray Adhesive

		(Contd. of pag
· Chemicals	known to cause developmental toxicity:	
108-88-3	toluene	
· Carcinoge	nic categories	
· EPA (Env	ironmental Protection Agency)	
67-64-1	acetone	I
108-88-3	toluene	II
78-93-3	butanone	I
1314-13-2	zinc oxide	D, I,
· TLV (Thr	eshold Limit Value established by ACGIH)	
67-64-1	acetone	A
108-88-3	toluene	A
· MAK (Ger	man Maximum Workplace Concentration)	
None of th	e ingredients is listed.	
· NIOSH-C	a (National Institute for Occupational Safety and Hea	ulth)
None of th	e ingredients is listed.	

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

- · Relevant phrases
- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to the central nervous system and the peripheral nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 11)

Printing date 02.08.2018 Version number 3 Revision: 22.06.2017

Trade name: GC Tray Adhesive

(Contd. of page 10)

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- · * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.