



Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: G2-BOND Universal 1-PRIMER
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxiliary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V. Interleuvenlaan 33 B-3001 Leuven

Tel. +32/(0)16/74.10.00 Fax +32/(0)16/40.26.84

msds@gc.dental

- · Further information obtainable from: Regulatory affairs
- · 1.4 Emergency telephone number:

National poison center for United Kingdom of Great Britain and Northern Ireland:

Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383

Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180

Penarth: +44 292 071 55 54

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Unst. Expl. H200 Unstable explosives.

Flam. Liq. 2 H225 Highly flammable liquid and vapour. Skin Corr. 1 H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

(Contd. on page 2)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND Universal 1-PRIMER

(Contd. of page 1)

#### · Hazard pictograms







GHS01

GHS05

GHS0'

### · Signal word Danger

### · Hazard-determining components of labelling:

acetone

2,2'-ethylenedioxydiethyl dimethacrylate

*Urethane Dimethacrylate (UDMA)* 

#### · Hazard statements

H200 Unstable explosives.

H225 Highly flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe dusts or mists.

*P280* Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

*P362+P364 Take off contaminated clothing and wash it before reuse.* 

*P373 DO NOT fight fire when fire reaches explosives.* 

P380 Evacuate area.

P401 Store in accordance with local/regional/national/international regulations.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

(Contd. on page 3)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND Universal 1-PRIMER

		(Contd. of page 2
Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 substance with a Community workplace exposure limit	25-<50%
CAS: 1830-78-0 EINECS: 217-388-4	2-Hydroxy-1,3 dimethacryloxypropane Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥10-<20%
CAS: 85590-00-7	methacryloyloxydecyl dihydrogen phosphate Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 68611-44-9 EINECS: 271-893-4	Silane, dichlorodimethyl-, reaction products with silica Nanoform: Spheroidal, amorphous nanoform, set including amorphous nanoforms, amorphous forms, surface- treated nanoforms	5-<10%
CAS: 109-16-0 EINECS: 203-652-6	2,2'-ethylenedioxydiethyl dimethacrylate Skin Sens. 1, H317	2.5-<5%
CAS: 75980-60-8 EINECS: 278-355-8 Index number: 015-203-00-X	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide Repr. 2, H361f	1-<2.5%
CAS: 128-37-0 EINECS: 204-881-4	Butylated hydroxytoluene Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Substance identified as having endocrine disrupting properties (II)	0.5-<1%
CAS: 1344-28-1 EINECS: 215-691-6	aluminium oxide Nanoform: Spheroidal, crystalline nanoform, crystalline forms, non-surface-treated nanoforms	0.5-<1%
CAS: 72869-86-4 EINECS: 276-957-5	Urethane Dimethacrylate (UDMA) Aquatic Chronic 2, H411; Skin Sens. 1B, H317	≥0.25-<0.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water.

Call a doctor immediately.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions

(Contd. on page 4)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND Universal 1-PRIMER

(Contd. of page 3)

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

*Use fire extinguishing methods suitable to surrounding conditions.* 

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Avoid contact with the eyes and skin.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Use neutralising agent.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

 $See \ Section \ 8 \ for \ information \ on \ personal \ protection \ equipment.$ 

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Prevent impact and friction.

Do not spray onto a naked flame or any incandescent material.

(Contd. on page 5)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND Universal 1-PRIMER

(Contd. of page 4)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store in a cool place.

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

#### 67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

#### · DNELs

#### 128-37-0 Butvlated hydroxytoluene

120-37-0 L	uiyiaiea nyaroxyi	oiuene
Dermal	DNEL dermal	0.5 mg/kg bw/day (man)
Inhalative	DNEL inhalation	3.5 mg/m3 (man)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- **Respiratory protection:** Suitable respiratory protective device recommended.
- · Hand protection



Protective gloves

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.


(Contd. on page 6)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND Universal 1-PRIMER

(Contd. of page 5)

· Eye/face protection



## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid Light yellow · Colour: Acetone-like · Odour: Not determined. · Odour threshold:

-95 °C · Melting point/freezing point: · Boiling point or initial boiling point and boiling range 55 °C

· Flammability Not applicable.

· Lower and upper explosion limit

2.6 Vol % (67-64-1 acetone) · Lower: · Upper: 13 Vol % (67-64-1 acetone)

-17 °C · Flash point:

· Auto-ignition temperature: Undetermined. Not determined. · Decomposition temperature:

· pH at 20 °C 1.5-2

· Viscosity:

· Kinematic viscosity Not determined. · Dynamic: Not determined.

·Solubility

Fully miscible. · water: · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure: Not determined.

· Density and/or relative density

 $0.94 \text{ g/cm}^3$ · Density at 20 °C: · Relative density Not determined. · Vapour density Not determined.

· Particle characteristics SiO2: Diameter particle structure = 2.5 - 50 nm (TEM,

d50, number-based)

Diameter agglomerate = 5 - 50 mm (laser diffraction dry

*module, d50, volume based)* 

Al2O3: Diameter particle structure = 2 - 100 nm (d50,

*number-based*)

68611-44-9 Silane, dichlorodimethyl-, reaction products with silica: Spheroidal, amorphous nanoform, set including amorphous nanoforms, amorphous forms,

surface-treated nanoforms

1344-28-1 aluminium oxide: Spheroidal, crystalline nanoform, crystalline forms, non-surface-treated

nanoforms

(Contd. on page 7)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND\_Universal\_1-PRIMER

(Contd. of page 6)

0 0	$\sim$ $\sim$		. •
. 4 /	( )thor	INTOV	mation
<i></i>	Ome	$uu_1u_1u_1$	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,

· Appearance:

· Form:

Important information on protection of health and

environment, and on safety.

• Ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

Risk of explosion by shock, friction, fire or other sources

of ignition.

· Solvent content:

• Organic solvents: 33.0 %
 • Water: 24.0 %
 • VOC (EC) 400.6 g/l

· Change in condition

• Evaporation rate Not determined.

· Information with regard to physical hazard classes

• Explosives Unstable explosives.

Flammable gases
Aerosols
Oxidising gases
Gases under pressure
Void
Void

· Flammable liquids Highly flammable liquid and vapour.

Flammable solids
Self-reactive substances and mixtures
Void
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Void
Substances and mixtures, which emit flammable gases in contact with water
Void
Oxidising liquids
Void

Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives

Void

Void

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND\_Universal\_1-PRIMER

		(Contd. of page 7)
· LD/LC5	0 valu	es relevant for classification:
67-64-1	aceton	ne e
Oral	LD50	5,800 mg/kg (rat (f+m))
Dermal	LD50	20,000 mg/kg (rabbit)
128-37-	0 Butyl	lated hydroxytoluene
Oral	LD50	>6,000 mg/kg (rat (f+m)) (OECD 401)
72869-8	6-4 Ur	ethane Dimethacrylate (UDMA)
Oral	LD50	>5,000 mg/kg (rat female) (OECD 401)
C1 ·	•	Construction C 1: 1 1 1

- · Skin corrosion/irritation Causes severe skin burns and eye damage.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause drowsiness or dizziness.
- · Additional toxicological information:
- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

· 11.2 Information on other hazards

· End	ocr	ine	disru	pting	pro	perties

128-37-0 Butylated hydroxytoluene

List II

### SECTION 12: Ecological information

· 12.1 Toxicity

## Aquatic toxicity: 128-37-0 Butylated hydroxytoluene

EC50/48h (static) 0.48 mg/l (daphnia magna) (OECD 202)

#### 72869-86-4 Urethane Dimethacrylate (UDMA)

EC50/48h (static) >1.2 mg/l (daphnia magna) (OECD 202)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Harmful to aquatic organisms

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND\_Universal\_1-PRIMER

(Contd. of page 8)

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN number or ID number ADR, IMDG, IATA	UN1993
· 14.2 UN proper shipping name · ADR	1993 FLAMMABLE LIQUID, N.O.S. (ACETONE), species
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (ACETONE)
· 14.3 Transport hazard class(es)	
· ADR	
· Class	3 (F1) Flammable liquids.
· Label	3
Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
· 14.7 Maritime transport in bulk according to IM instruments	IO Not applicable.

(Contd. on page 10)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND\_Universal\_1-PRIMER

Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
- · · <del>-</del>	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE), 3, I.

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category Pla EXPLOSIVES
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 10 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

- · Relevant phrases
- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 11)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND Universal 1-PRIMER

(Contd. of page 10)

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Unst. Expl.: Explosives – Unstable explosive Flam. Liq. 2: Flammable liquids – Category 2

Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

 $\label{lem:aquatic charges} \textit{Aquatic Chronic 3: Hazardous to the aquatic environment-long-term aquatic hazard-Category 3}$ 

#### · Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- \* Data compared to the previous version altered.

This version replaces all previous versions.

#### Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.