



Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name:

#### G2-BOND Universal 2-BOND

Nanoform

- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxiliary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V.

Interleuvenlaan 33

B-3001 Leuven

Tel. +32/(0)16/74.10.00

Fax + 32/(0)16/40.26.84

msds@gc.dental

- · Information department: Regulatory affairs
- · 1.4 Emergency telephone number: International: +01-813-248-0585 (ChemTel Inc.)

### SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361f Suspected of damaging fertility.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labeled according to the CLP regulation.

· Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms









GHS05 G

GHS07

GHS08 (

8 CHS0

- · Signal word Danger
- · Hazard-determining components of labeling: (1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate

(Contd. on page 2)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND Universal 2-BOND

(Contd. of page 1)

*Urethane Dimethacrylate (UDMA)* 

2-Hydroxy-1,3 dimethacryloxypropane

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

· Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H361f Suspected of damaging fertility.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

*P362+P364 Take off contaminated clothing and wash it before reuse.* 

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

#### · Determination of endocrine-disrupting properties

128-37-0 Butylated hydroxytoluene

List II

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

Dangerous	components:	
1830-78-0	2-Hydroxy-1,3 dimethacryloxypropane	25-<50%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1
72869-86-4	Urethane Dimethacrylate (UDMA)	25-<50%
	Aquatic Chronic 2, H411; Skin Sens. 1B, H317	1
1565-94-2	(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	10-<25%
	Eye Dam. 1, H318; Skin Sens. 1, H317	1
68909-20-6	Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	5-<10%
	STOT RE 2, H373, EUH066	
75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	≥3-<5%
	Repr. 2, H361f	1
128-37-0	Butylated hydroxytoluene	1-<2.5%
	Aquatic Acute 1, H400; Aquatic Chronic 1, H410 (II)	
	(Col	ntd. on page 3

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND Universal 2-BOND

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eve contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water.

If symptoms persist consult doctor.

Call a doctor immediately.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Avoid contact with the eyes and skin.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

(Contd. on page 4)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND Universal 2-BOND

(Contd. of page 3)

Do not allow to penetrate the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

Dispose of the collected material according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage.
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs						
128-37-0 Butylated hydroxytoluene						
Dermal	DNEL dermal	0.5 mg/kg bw/day (man)				
Inhalative	DNEL inhalation	3.5 mg/m3 (man)				

- · Additional information: The lists that were valid during the creation were used as basis.
- · 8.2 Exposure controls
- · Additional information about design of technical systems: No further data; see section 7.
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

· Breathing equipment: Suitable respiratory protective device recommended.

(Contd. on page 5)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND Universal 2-BOND

(Contd. of page 4)

#### Protection of hands:



Protective gloves

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not applicable.

· Eye protection:



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Color:
Odor:
Odorless
Odor threshold:
Melting point/Melting range:
Boiling point/Boiling range:
Undetermined.
Undetermined.

· Explosion limits:

Lower:

Upper:
Not determined.

Flash point:

Not applicable.

Auto igniting:

Undetermined.

Decomposition temperature:

Not determined.

Not determined.

Not determined.

· Viscosity:

Kinematic: Not determined.Dynamic: Not determined.

· Solubility in / Miscibility with

· Flammability (solid, gaseous):

Water: Fully miscible.
 Partition coefficient (n-octanol/water): Not determined.
 Vapor pressure: Not determined.

· Density and/or relative density

• Density at 20 °C: 1.2 g/cm³
• Relative density Not determined.

(Contd. on page 6)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND\_Universal\_2-BOND

	(Contd. of page
Vapor density	Not determined.
Particle characteristics	SiO2: Diameter particle structure = 2.5 - 50 nm (TEI
	d50, number-based)
	Diameter agglomerate = $5 - 50$ mm (laser diffraction d
	module, d50, volume based)
	68909-20-6 Silanamine, 1,1,1-trimethyl-1
	(trimethylsilyl)-, hydrolysis products with silic
	Spheroidal, amorphous nanoform, set including
	amorphous nanoforms, amorphous forms, surfac
	treated nanoforms
9.2 Other information	
Appearance:	71
Form:	Liquid
Important information on protection of hea	utn ana
environment, and on safety.	Product is not selfigniting.
Ignition temperature: Danger of explosion:	Product is not seifighting.  Product does not present an explosion hazard.
Solvent content:	Troduct does not present an expression nazara.
VOC (EC)	$0.0 \ g/l$
Change in condition	0.0 8/1
Evaporation rate	Not determined.
Information with regard to physical hazard cla	usses
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammab	
in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void Void
Corrosive to metals	Void
Desensitised explosives	Void

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 7)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND Universal 2-BOND

(Contd. of page 6)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.

### · LD/LC50 values that are relevant for classification:

### 72869-86-4 Urethane Dimethacrylate (UDMA)

Oral LD50 >5,000 mg/kg (rat female) (OECD 401)

### 128-37-0 Butylated hydroxytoluene

Oral | LD50 | >6,000 mg/kg (rat (f+m)) (OECD 401)

- · on the skin: Causes skin irritation.
- · on the eye: Causes serious eye damage.
- · Sensitization: May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Suspected of damaging fertility.
- · Specific target organ toxicity single exposure May cause respiratory irritation.
- · Specific target organ toxicity repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

· 11.2 Information on other hazards

#### · Endocrine disrupting properties

128-37-0 Butylated hydroxytoluene

List II

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

### 72869-86-4 Urethane Dimethacrylate (UDMA)

EC50/48h (static) >1.2 mg/l (daphnia magna) (OECD 202)

## 128-37-0 Butylated hydroxytoluene

EC50/48h (static) 0.48 mg/l (daphnia magna) (OECD 202)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish

(Contd. on page 8)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND\_Universal\_2-BOND

(Contd. of page 7)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

SECTION 14: Transport inform	ation
14.1 UN-Number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name	
DOT	not regulated
ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (Urethane Dimethacrylate (UDMA))
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI. N.O.S. (Urethane Dimethacrylate (UDMA), Butylate hydroxytoluene), MARINE POLLUTANT
IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI N.O.S. (Urethane Dimethacrylate (UDMA))
Class Label	9 (M6) Miscellaneous dangerous substances and articles 9
IMDG, IATA	
<b>1 1 1 1 1 1 1 1 1 1</b>	
Class	9 Miscellaneous dangerous substances and articles
Label	9
14.4 Packing group	
ADR, IMDG, IATA	III

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND\_Universal\_2-BOND

	(Contd. of page
14.5 Environmental hazards:	
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles
Hazard identification number (Kemler code):	90
EMS Number:	F- $A$ , $S$ - $F$
Stowage Category	A
14.7 Transport in bulk according to Annex II of	of .
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	(-)
<i>IMDG</i>	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANC
Ç	LIQUID, N.O.S. (URETHANE DIMETHACRYLATE (UDMA) 9, III

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 10)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND Universal 2-BOND

(Contd. of page 9) Carcinogenic categories · EPA (Environmental Protection Agency) None of the ingredients is listed. · TLV (Threshold Limit Value) 128-37-0 Butylated hydroxytoluene A4· MAK (German Maximum Workplace Concentration) 128-37-0 Butylated hydroxytoluene 4 · NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

- · Relevant phrases
- Causes skin irritation. H315
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eve irritation.
- H335 May cause respiratory irritation.
- H361f Suspected of damaging fertility.
- May cause damage to organs through prolonged or repeated exposure. H373
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 11)

Printing date 30.06.2023 Version number 2 (replaces version 1) Revision: 30.06.2023

Trade name: G2-BOND\_Universal\_2-BOND

(Contd. of page 10)

#### · Classification according to Regulation (EC) No 1272/2008 Calculation method

- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Date of previous version 30.06.2023
- · Version number of previous version: 1
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

#### ·Sources

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- \* Data compared to the previous version altered.

This version replaces all previous versions.

#### Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.