

Printing date 15.05.2023 Version number 2 (replaces version 1) Revision: 17.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GC RELINE II REMOVER FOR RESIN
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxiliary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V. Interleuvenlaan 33

B-3001 Leuven

Tel. +32/(0)16/74.10.00

Fax + 32/(0)16/40.26.84

msds@gc.dental

- · Information department: Regulatory affairs
- · 1.4 Emergency telephone number: International: +01-813-248-0585 (ChemTel Inc.)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labeled according to the CLP regulation.

· Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms





GHS02

- · Signal word Danger
- · Hazard-determining components of labeling:

Methyl methacrylate ethyl acetate

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

(Contd. on page 2)

Printing date 15.05.2023 Version number 2 (replaces version 1) Revision: 17.11.2022

Trade name: GC RELINE II REMOVER FOR RESIN

(Contd. of page 1)

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Da	angerou	s components:	
14	11-78-6	ethyl acetate	50-<75%
		Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	
8	80-62-6	Methyl methacrylate	25-<50%
		Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	

[•] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Protect unharmed eye.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

(Contd. on page 3)

Printing date 15.05.2023 Version number 2 (replaces version 1) Revision: 17.11.2022

Trade name: GC RELINE II REMOVER FOR RESIN

(Contd. of page 2)

- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources

Avoid contact with the eyes and skin.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the collected material according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eves and skin.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray on a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

(Contd. on page 4)

Printing date 15.05.2023 Version number 2 (replaces version 1) Revision: 17.11.2022

Trade name: GC RELINE II REMOVER FOR RESIN

(Contd. of page 3)

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with limit values that require monitoring at the workplace:	
<i>141-78-</i>	-6 ethyl acetate
IOELV	Short-term value: 1468 mg/m³, 400 ppm
	Long-term value: 734 mg/m³, 200 ppm
80-62-6	Methyl methacrylate
IOELV	Short-term value: 100 ppm
	Long-term value: 50 ppm
· DNELs	•
80-62-6	Methyl methacrylate
Dermal	DNFL dermal 13.67 mg/kg bw/day (man) (worker 1 te syst)

Dermal	DNEL dermal	13.67 mg/kg bw/day (man) (worker, l. te., syst.)			
Inhalative	DNEL inhalation	208 mg/m3 (air) (worker, l. te., syst.)			

- · Additional information: The lists that were valid during the creation were used as basis.
- · 8.2 Exposure controls
- · Additional information about design of technical systems: No further data; see section 7.
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

- · Breathing equipment: Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.


(Contd. on page 5)

Printing date 15.05.2023 Version number 2 (replaces version 1) Revision: 17.11.2022

Trade name: GC RELINE II REMOVER FOR RESIN

(Contd. of page 4)

Eye protection:



SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Color:
Odor:
Odor threshold:
Fluid
Clear
Fruit-like
Not determined.

· Melting point/Melting range: -83 °C
· Roiling point/Roiling range: Undeter

Boiling point/Boiling range:
 Flammability (solid, gaseous):
 Undetermined.
 Highly flammable.

· Explosion limits:

Lower: 2.1 Vol %
 Upper: 12.5 Vol %
 Flash point: -1 °C

· Auto igniting: Undetermined.
· Decomposition temperature: Not determined.
· pH-value: Not determined.

· Viscosity:

Kinematic: Not determined.Dynamic: Not determined.

· Solubility in / Miscibility with

· Water: Insoluble.

Partition coefficient (n-octanol/water):
 Vapor pressure:
 Not determined.
 Not determined.

Density and/or relative density

Density: Not determined.
Relative density Not determined.
Vapor density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid · Important information on protection of health and

environment, and on safety.

• Ignition temperature: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Solvent content:

• Organic solvents: 70.0 % • VOC (EC) 700.0 g/l

· Change in condition

• Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives VoidFlammable gases Void

(Contd. on page 6)

Printing date 15.05.2023 Version number 2 (replaces version 1) Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 5)

· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammab	ole gases
in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
Desensitised explosives	Void
<u>-</u>	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values that are relevant for classification:				
141-78-6 e	thyl acetat	te			
Oral	LD50	4,935 mg/kg (rabbit)			
Inhalative	LC50/4 h	1,600 mg/l (rat (f+m))			
80-62-6 M	ethyl meth	acrylate			
Oral	LD50	6,000 mg/kg (rabbit)			
Dermal	LD50	>5,000 mg/kg (rab)			
		29.8 mg/l (rat (f+m))			

- · on the skin: Causes skin irritation.
- · on the eye: Causes serious eye irritation.
- · Sensitization: May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · Specific target organ toxicity single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

· Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met. (Contd. on page 7)

– EU

Printing date 15.05.2023 Version number 2 (replaces version 1) Revision: 17.11.2022

Trade name: GC RELINE II REMOVER FOR RESIN

(Contd. of page 6)

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

- · Repeated dose toxicity No further relevant information available.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

 No further relevant information available.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· European	waste catalogue
	WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE)
	wastes from natal care, diagnosis, treatment or prevention of disease in humans
18 01 06*	chemicals consisting of or containing hazardous substances

- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

EU

Version number 2 (replaces version 1) Printing date 15.05.2023 Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 7)

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN1173
14.2 UN proper shipping name DOT ADR IMDG, IATA	Ethyl acetate 1173 ETHYL ACETATE ETHYL ACETATE
14.3 Transport hazard class(es)	
ADR	
Class Label	3 (F1) Flammable liquids
IMDG, IATA	
Class	3 Flammable liquids
Label	3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category	Warning: Flammable liquids 33 F-E,S-D B
14.7 Transport in bulk according to Annex II o	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2
Tunnel restriction code	D/E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

Printing date 15.05.2023 Version number 2 (replaces version 1) Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 8)

· UN "Model Regulation":

UN 1173 ETHYL ACETATE, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 Methyl methacrylate

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

80-62-6 Methyl methacrylate

E, NL

· TLV (Threshold Limit Value)

80-62-6 Methyl methacrylate

A4

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

(Contd. on page 10)

Printing date 15.05.2023 Version number 2 (replaces version 1) Revision: 17.11.2022

Trade name: GC RELINE II REMOVER FOR RESIN

(Contd. of page 9)

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

- · Relevant phrases
- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- Date of previous version 17.11.2022
- · Version number of previous version: 1
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

Flam. Liq. 2: Flammable liquids - Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- · Sources
- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part.

(Contd. on page 11)

Printing date 15.05.2023 Version number 2 (replaces version 1) Revision: 17.11.2022

Trade name: GC_RELINE_II_REMOVER_FOR_RESIN

(Contd. of page 10)

Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

EU -