

Printing date 02.08.2018 Version number 3 Revision: 21.06.2017

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: GC Unifast III Liquid
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

GC EUROPE N.V. Interleuvenlaan 33 B-3001 Leuven Tel. +32/(0)16/74.10.00

Fax + 32/(0)16/40.26.84

msds@gc.dental

- · Further information obtainable from: Regulatory affairs
- · 1.4 Emergency telephone number:

National poison center for United Kingdom of Great Britain and Northern Ireland:

Belfast: +44 28 90 63 2032 Birmingham: +44 121 507 4123 Edinburgh: +44 131 242 1383

Newcastle Upon Tyne: +44 191 2606182/+44 191 2606180

Penarth: +44 292 071 55 54

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Exempt from requirements - product regulated as a medical device or an in vitro diagnostic medical device.

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

Exempt from requirements - product regulated as a medical device or an in vitro diagnostic medical device. The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

· Signal word Danger

Printing date 02.08.2018 Version number 3 Revision: 21.06.2017

Trade name: GC Unifast III Liquid

(Contd. of page 1)

#### · Hazard-determining components of labelling:

Methyl methacrylate

Ethyleneglycol dimethacrylate

2-(2H-benzotriazol-2-yl)-p-cresol

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P272 Contaminated work clothing should not be allowed out of the workplace.

*P280* Wear protective gloves / eye protection / face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · 2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

#### · 3.2 Chemical characterisation: Mixtures

· Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

· Dangerous components:		
CAS: 80-62-6	Methyl methacrylate	75-<90%
EINECS: 201-297-1	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE	
Index number: 607-035-00-6	3, H335	
CAS: 99-97-8	N,N-dimethyl-p-toluidine	2.5-<5%
EINECS: 202-805-4	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT RE	
Index number: 612-056-00-9	2, H373; Aquatic Chronic 3, H412	
CAS: 97-90-5	Ethyleneglycol dimethacrylate	1-<2.5%
EINECS: 202-617-2	Skin Sens. 1, H317; STOT SE 3, H335	
Index number: 607-114-00-5		
CAS: 3290-92-4	Propylidynetrimethyl trimethacrylate	1-<2.5%
EINECS: 221-950-4	Aquatic Chronic 2, H411	
CAS: 2440-22-4	2-(2H-benzotriazol-2-yl)-p-cresol	0.5-<1%
EINECS: 219-470-5	Acute Tox. 2, H330; Aquatic Chronic 1, H410; Skin Sens. 1, H317	
CAS: 128-37-0	Butylated hydroxytoluene	0.5-<1%
EINECS: 204-881-4	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
CAS: 1879-09-0	6-tert-butyl-2,4-xylenol	0.5-<1%
EINECS: 217-533-1	Acute Tox. 2, H310; STOT RE 2, H373; Aquatic Chronic 2, H411;	
	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
	(Con	td on nage 3

(Contd. on page 3)

Printing date 02.08.2018 Version number 3 Revision: 21.06.2017

Trade name: GC Unifast III Liquid

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Do not use mouth to mouth or mouth to nose resuscitation.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water.

If symptoms persist consult doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · 4.2 Most important symptoms and effects, both acute and delayed Allergic reactions
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Avoid contact with the eyes and skin.

Wear protective clothing.

(Contd. on page 4)

Printing date 02.08.2018 Version number 3 Revision: 21.06.2017

Trade name: GC Unifast III Liquid

(Contd. of page 3)

#### · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

 $\cdot$  7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:	
80-62	-6 Methyl methacrylate
	Short-term value: 416 mg/m³, 100 ppm
	Long-term value: 208 mg/m³, 50 ppm

#### · DNELs

#### 80-62-6 Methyl methacrylate

Dermal	DNEL dermal	13.67 mg/kg bw/day (man) (worker, l. te., syst.)
Inhalative	DNEL inhalation	208 mg/m3 (air) (worker, l. te., syst.)

(Contd. on page 5)

Printing date 02.08.2018 Version number 3 Revision: 21.06.2017

Trade name: GC Unifast III Liquid

			(Contd. of page 4
128-37-0 But	ylated hydroxyt	oluene	
Dermal Di	NEL dermal	0.5 mg/kg bw/day (man)	
Inhalative Di	NEL inhalation	3.5 mg/m3 (man)	
1879-09-0 6-1	tert-butyl-2,4-xy	lenol	
Inhalative Di	NEL inhalation	0.14 mg/m3 (man)	
· PNECs			
99-97-8 N,N-	dimethyl-p-tolu	idine	
PNEC Aqua	152.59 μg/L	(freshwater)	
3290-92-4 Pr	opylidynetrimet	hyl trimethacrylate	
PNEC Air	- mg/L (air)	mg/L (air)	
PNEC Aqua	2.76 μg/L (f	reshwater)	
	20 μg/L (int	ermittent releases)	
	0.276 μg/L (	marine water)	
PNEC Predat	C Predator - mg/kg (Predator)		
PNEC STP	10 mg/L (Sewage Treatment Plants)		
PNEC Sedime	ent 0.4951 mg/k	g sed dw (freshwater)	
	0.04951 mg	kg sed dw (marine water)	
PNEC Soil	0.0974 mg/k	0.0974 mg/kg soil dw (soil)	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Store protective clothing separately.

- · Respiratory protection: Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.


(Contd. on page 6)

Printing date 02.08.2018 Version number 3 Revision: 21.06.2017

Trade name: GC Unifast III Liquid

 $(Contd.\ of\ page\ 5)$ 

· Eye protection:



9.1 Information on basic physical and c General Information	chemical properties
Appearance:	
Form:	Liquid
Colour:	Clear
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	2: 100 °C
Flash point:	10 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	Undetermined.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
Vapour pressure:	Not determined.
Density at 20 °C:	0.9 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Insoluble.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

Printing date 02.08.2018 Version number 3 Revision: 21.06.2017

Trade name: GC Unifast III Liquid

(Contd. of page 6)

· 9.2 Other information

No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	· LD/LC50 values relevant for classification:		
80-62-6 M	80-62-6 Methyl methacrylate		
Oral	LD50	6000 mg/kg (rabbit)	
Dermal	LD50	>5000 mg/kg (rab)	
Inhalative	LC50/4 h	29.8  mg/l  (rat  (f+m))	
99-97-8 N,	N-dimethy	rl-p-toluidine	
Oral	LD50	1650 mg/kg (rat (f+m))	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	1.4  mg/l  (rat  (f+m))	
97-90-5 Et	97-90-5 Ethyleneglycol dimethacrylate		
Oral	LD50	8700 mg/kg (rat (f+m))	
Dermal	LD50	>2000 mg/kg (rat (f+m))	
2440-22-4	2440-22-4 2-(2H-benzotriazol-2-yl)-p-cresol		
Oral	LD50	10000 mg/kg (rat (f+m))	
Inhalative	LC50/4 h	0.59  mg/l  (rat  (f+m))	
128-37-0 B	Butylated h	ydroxytoluene	
Oral	LD50	> 6000 mg/kg (rat (f+m)) (OECD 401)	
1879-09-0	1879-09-0 6-tert-butyl-2,4-xylenol		
Oral	LD50	910 mg/kg (rat (f+m)) (OECD 401)	
Dermal	LD50	< 200 mg/kg (rabbit) (OECD 402)	
<b>D</b>	witant offor	· .	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Repeated dose toxicity No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

(Contd. on page 8)

Printing date 02.08.2018 Version number 3 Revision: 21.06.2017

Trade name: GC Unifast III Liquid

(Contd. of page 7)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity	:
99-97-8 N,N-di	methyl-p-toluidine
LC50/96h	46 mg/L (fish)
3290-92-4 Prop	ylidynetrimethyl trimethacrylate
LC50/96h (dyna	umic) >1 mg/L (Oncorhvnchus mykiss) (OECD Guideline 203 (Fish, Acute Toxicity Test))
128-37-0 Butylo	nted hydroxytoluene
EC50/48h (stati	c) 0.48 mg/l (daphnia magna) (OECD 202)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	· European waste catalogue		
	WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care)		
18 01 00	wastes from natal care, diagnosis, treatment or prevention of disease in humans		
18 01 06*	chemicals consisting of or containing dangerous substances		
	(Contd. on page 0)		

(Contd. on page 9)

Printing date 02.08.2018 Version number 3 Revision: 21.06.2017

Trade name: GC Unifast III Liquid

(Contd. of page 8)

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN1247
14.2 UN proper shipping name ADR IMDG, IATA	1247 METHYL METHACRYLATE MONOMER, STABILIZED METHYL METHACRYLATE MONOMER, STABILIZED
14.3 Transport hazard class(es)	
ADR	
Class Label	3 (F1) Flammable liquids.
IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Danger code (Kemler): EMS Number:	Warning: Flammable liquids. 339 F-E,S-D
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	r Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category Tunnel restriction code	2 D/E

Printing date 02.08.2018 Version number 3 Revision: 21.06.2017

Trade name: GC Unifast III Liquid

(Contd. of page 9)

· IMDG
· Limited quantities (LQ)
· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation":

UN 1247 METHYL METHACRYLATE MONOMER,

STABILIZED, , II

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

(Contd. on page 11)

Version number 3 Printing date 02.08.2018 Revision: 21.06.2017

Trade name: GC Unifast III Liquid

(Contd. of page 10)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 3: Acute toxicity - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 2: Acute toxicity - Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- \* Data compared to the previous version altered.

This version replaces all previous versions.

#### Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.